



NOTE When the sensor is mounted at higher than 3.0m, set the Sensitivity to "H (high)".

Model	: OM-105C / 106C	Output	: Form C relay
Cover color	: Silver / Black		: 50V 0.3A Max.(Resistance load)
Mounting height	: 2.0 (6'7") to 3.5m (11'5")	Output hold time	: 0.5sec. / 2.0sec.
Detection method	: Microwave doppler effect	Response time	: < 0.3sec.
Transmitter frequency	: 24.125GHz	Operating humidity	: < 80%
Transmitter radiated power	: < 20dBm	Operating temperature	: -20°C to +55°C(-4°F to 131°F)
Detection area	: See Detection area	IP rate	: IP54
Vertical adjustment	: +10° to +70° (Header mount) +20° to +80° (Ceiling mount)	Weight	: 140g (4.9oz)
Horizontal adjustment	: 30° to left or right	Accessories	: 1 Cable 3m (9'10") 1 Operation manual 2 Mounting screws 1 Mounting template 1 Narrow lens*
Power supply	: 12 to 24VAC(±10%) 12 to 30VDC(±10%)		
Power consumption	: < 1.5W(< 2VA at AC)		
Minimum speed	: 5cm(1 15/16") / sec.		
Operation indicator	: Green / Stand-by Red / Detection Green blinking / Set-up		* At the back of housing cover

NOTE The specifications herein are subject to change without prior notice due to improvements.

